

CANADIAN ETV PROGRAM VERIFIED

Eco Waste Oxidizer

Technology Fact Sheet for Eco Waste Solutions



Performance Claim

The Eco Waste Oxidizer, manufactured by Eco Burn Inc. o/a Eco Waste Solutions, is a two-stage thermal gasification system capable of meeting the stack emission criteria specified below, when used to incinerate municipal solid waste, and when the minimum temperature and minimum residence time in the afterburner are 1,000°C and 3.2 seconds, respectively.

Parameter	Stack Emission Criteria	Unit
Particulate	12	mg/Rm ³
Pb + Mn + Cr + Cu	1	mg/Rm ³
As + Ni	0.02	mg/Rm ³
Cd + Hg	0.1	mg/Rm ³
Dioxin / Furan *	0.09	ng I-TEQ/Rm ³
SO ₂ **	39	mg/Rm ³
NOx	136	mg/Rm ³
CO	1.3	mg/Rm ³

* I-TEQ refers to international toxicity equivalent factor (2,3,7,8-TCDD)

** Emissions exclude diesel fuel auxiliary burner SO₂ and NOx contributions.

R indicates the reference measurement conditions for emissions, which are: temperature = 25°C, pressure = 101.3 kPa, and O₂ content = 11% dry.

Technology Description

The Eco Waste Oxidizer is a batch-mode two-stage thermal oxidation system for incinerating solid waste. In the first stage, waste is oxidized in the combustion chamber by means of a gas or oil fired burner. Off gases from the first stage are combusted in the second stage (afterburner) and then emitted via a stack. Critical process parameters in both stages are computer controlled. The complete oxidation cycle, which consists of loading, combustion, cooling and ash removal, occurs over twenty four hours. The actual oxidation process occurs over an 8 to 10 hour period.

Environmental Technology Verification

Technology Application

The Eco Waste Oxidizer can be used for the thermal oxidation of municipal, medical and industrial waste. The verified performance claim is based on the incineration of municipal solid waste.

Performance Conditions

The average operating conditions in the afterburner during the claim assessment period were:

Run	Temperature (°C)	Residence Time (sec)
1	999	3.1
2	996	3.1
3	1,002	3.2

Verification

The data set analyzed for claim verification was generated for a compliance test performed on full-scale system in Burlington, Ontario. The test was performed by EcoSphere Environmental Inc., between May 15 - 17, 1996, with all protocols accepted by the Ontario Ministry of the Environment and Energy (MOEE). The loadings to the incinerator on the three test days were 794 kg, 801 kg, and 1,062 kg of municipal solid waste. The verification of the performance claim based on this data was carried out by the Water Technology International Corporation (WTI). The data was analyzed using various statistical methods, including one-tailed and two-tailed hypothesis tests.

What is the Canadian ETV Program?

The Canadian Environmental Technology Verification (ETV) Program is delivered by GLOBE Performance Solutions under a license agreement from Environment Canada. The Canadian ETV Program is designed to support Canada's environment industry by providing credible and independent verification of technology performance claims.

For more information on the Eco Waste Oxidizer please contact:

Eco Burn Inc. o/a
Eco Waste Solutions
14 - 5195 Harvester Road
Burlington, Ontario
L7L 6E9 Canada
Tel: (905) 634-7022
Toll Free: 1-866-326-2876
www.ecosolutions.com

Canadian ETV Program Contact Information:

c/o GLOBE Performance Solutions
World Trade Centre
404 - 999 Canada Place
Vancouver, BC
V6C 3E2 Canada
Tel: 604-695-5018
Toll Free: 1-855-695-5018
etv@globepformance.com
www.etvcanada.ca



Limitation of Verification

Environment Canada, the Canadian ETV Program, and the Verification Expert provide the verification services solely on the basis of the information supplied by the applicant or vendor and assume no liability thereafter. The responsibility for the information supplied remains solely with the applicant or vendor and the liability for the purchase, installation, and operation (whether consequential or otherwise) is not transferred to any other party as a result of the verification.